



oneLED

LED spotlight with global adapter for mounting on 3-phase track.

Lightfixture body made of aluminium. Passive cooling of the LED chip for optimum service life and reliability.


Lens and reflector that creates a well-balanced light pattern with very high efficiency.

Material
Colour temp [K]
Optimal Colour temp [K]


Design LED life
CRI
Initial MacAdam
Nominal Voltage
Form protection
Weight

Die-cast aluminium
3000 K B BBL
2700 K, 3000 K, 4000 K,
5000 K, Food Meat / Vegetable
L70 B10 > 50 000 h (T₀ 25°)
90
2 SDCM
230/240 V, 50 Hz
IP 20. Class I. CE-approved
1,2 kg

Dimensions [mm]



Colours



Item No.	Description	Painting colour	Power	Lumen output	EEC	LED Colour	Amount/Fuse 16 A C-type	Amount/Fuse 16 A B-type
150805-930-1201	oneLED, Spot 12°	White	31 W	3008 lm	A+	3000 K B BBL	51	32
150805-930-2401	oneLED, Medium 24°	White	31 W	3019 lm	A+	3000 K B BBL	51	32
150805-930-3801	oneLED, Flood 38°	White	31 W	3052 lm	A+	3000 K B BBL	51	32
150805-930-1202	oneLED, Spot 12°	Grey	31 W	3008 lm	A+	3000 K B BBL	51	32
150805-930-2402	oneLED, Medium 24°	Grey	31 W	3019 lm	A+	3000 K B BBL	51	32
150805-930-3802	oneLED, Flood 38°	Grey	31 W	3052 lm	A+	3000 K B BBL	51	32
150805-930-1203	oneLED, Spot 12°	Black	31 W	3008 lm	A+	3000 K B BBL	51	32
150805-930-2403	oneLED, Medium 24°	Black	31 W	3019 lm	A+	3000 K B BBL	51	32
150805-930-3803	oneLED, Flood 38°	Black	31 W	3052 lm	A+	3000 K B BBL	51	32

Caleidoscope

Östra Sandgatan 14 - 252 27 Helsingborg - Sweden - sales@caleidoscope.se - www.caleidoscope.se - Tel +46(0)42 311 18 10