



plainLED AC

AC-LED spotlight with global adapter for mounting on 3-phase track.

Lightfixture body made of aluminium.

Passive cooling of the LED chip for optimum service life and reliability.


Lens and reflector that creates a well-balanced light pattern with very high efficiency.

Color: white, black or gray.


Material
Colour temp [K]
Design LED life
CRI
Initial MacAdam
Power
Nominal Voltage
Form protection
Weight

Die-cast aluminium
 3000 K
 L70 B50 > 50 000 h (T_a 25°)
 80
 3 SDCM
 30 W
 230/240 V, 50 Hz
 IP 20. Class I. CE-approved
 0,7 kg

Dimensions [mm]



Colours



Item No.	Description	Painting colour	Power	Lumen output	EEC	LED Colour	Amount/Fuse 16 A C-type	Amount/Fuse 16 A B-type
150808-830-1201	plainLED AC, Spot 12°	White	30 W	1956 lm	A	3000 K	51	32
150808-830-2401	plainLED AC, Medium 24°	White	30 W	1960 lm	A	3000 K	51	32
150808-830-3801	plainLED AC, Flood 38°	White	30 W	1968 lm	A	3000 K	51	32
150808-830-1202	plainLED AC, Spot 12°	Grey	30 W	1956 lm	A	3000 K	51	32
150808-830-2402	plainLED AC, Medium 24°	Grey	30 W	1960 lm	A	3000 K	51	32
150808-830-3802	plainLED AC, Flood 38°	Grey	30 W	1968 lm	A	3000 K	51	32
150808-830-1203	plainLED AC, Spot 12°	Black	30 W	1956 lm	A	3000 K	51	32
150808-830-2403	plainLED AC, Medium 24°	Black	30 W	1960 lm	A	3000 K	51	32
150808-830-3803	plainLED AC, Flood 38°	Black	30 W	1968 lm	A	3000 K	51	32

Caleidoscope