



## rawLED G1

LED spotlight with global adapter for mounting on 3-phase track.

Lightfixture body made of aluminium.

Passive cooling of the LED chip for optimum service life and reliability.


Color: white, black or grey.

**Material**  
**Colour temp [K]**  
**Design LED life**  
**CRI**  
**Initial MacAdam**  
**Nominal Voltage**  
**Form protection**  
**Weight**

**Dimensions [mm]**

**Colours**

Die-cast aluminium  
 3000 K / 4000 K  
 L70 B10 > 50 000 h (T<sub>0</sub> 25°)  
 80  
 3 SDCM  
 230/240 V, 50 Hz  
 IP 20, Class I, CE-approved  
 1,8 kg



Item No.	Description	Painting colour	Power	Lumen output	EEC	LED Colour	Amount/Fuse 16 A C-type	Amount/Fuse 10 A C-type
019-83001-1801	rawLED, Spot 18°	White	34 W	2750 lm	A+	3000 K	51	32
019-83001-5201	rawLED, Flood 52°	White	34 W	2750 lm	A+	3000 K	51	32
019-84001-1801	rawLED, Spot 18°	White	34 W	2750 lm	A+	4000 K	51	32
019-84001-5201	rawLED, Flood 52°	White	34 W	2750 lm	A+	4000 K	51	32

*Caleidoscope*