



varioLED KIT

Small LED kit with 3 downlight units connected to one driver.

Passive cooling of LED chip for optimal service life and reliability.

Comes complete with 3.0 meter cable and pre-mounted drives with quick connectors.

Each drive can run two (as minimum) up to three fixtures.

Included a bypasses connector if systems shall run on only two downlight.

Material
Colour temp [K]
Design LED life
CRI
Initial MacAdam
Nominal Voltage
Form protection
Weight
Dial


Cut out [mm]

Powder coated aluminium
 3000 K
 L70 B50 > 50 000 h (T_a 25°)
 +80
 3 SDCM
 230/240 V, 50 Hz
 IP 20. Class III. CE-approved
 0,95 kg
 On request

ø 85 mm



System overview



Item No.	Description	Reflector /Beam	Painting colour	Energy consumption	Lumen output	EEC	Colour temperature, CRI
018-830-356-01	varioLED KIT 3 x 6,5 W, White	Flood	White	3 x 6,5 W	3 x 485 lm	A+	3000 K, CRI > 80
018-830-356-02	varioLED KIT 3 x 6,5 W, Grey	Flood	Grey	3 x 6,5 W	3 x 485 lm	A+	3000 K, CRI > 80
018-830-356-03	varioLED KIT 3 x 6,5 W, Black	Flood	Black	3 x 6,5 W	3 x 485 lm	A+	3000 K, CRI > 80

Caleidoscope

Östra Sandgatan 14 - 252 27 Helsingborg - Sweden - sales@caleidoscope.se - www.caleidoscope.se - Tel +46(0)42 311 18 10