ultraBEAM LED 8000 Multi

A multifunctional energyefficient LED general lighting luminaire for installation on cable trays, suspended ceilings or wire.

Double parabolic optics for ceiling heights from 3 to 7 meters. Available with narrow or medium beam reflector. High anit-glare.

LED general lighting fixture equipped with 5 × 2.5 mm2 through wiring.

Cables through the gables. Easy installation thanks to the fold-down panels on each side that allows Intallation of cable on already mounted luminaire.

Protection class IP22.

7-years LED warranty.

Art. No:	Description	Colour	Power	Lumen Out	CCT (Kelvin)	Dimension	System
150130 830 13 14	ultraBEAM LED 7000 lm, 830, WIDE, 5x2,5 mm2, White	White	68 W	7 225 lm	3000 K, Ra > 83	L1900xB70xH80 mm	Wire / Direct
150130 840 13 14	ultraBEAM LED 7000 lm, 840, BRED, 5x2,5 mm2 , White	White	68 W	7 349 lm	4000 K, Ra > 83	L1900xB70xH80 mm	Wire / Direct
150130 830 23 14	ultraBEAM LED 7000 lm, 830, SMAL, 5x2,5 mm2, White	White	68 W	7 225 lm	3000 K, Ra > 83	L1900xB70xH80 mm	Wire / Direct
150130 840 23 14	ultraBEAM LED 7000 lm, 840, SMAL, 5x2,5 mm2, White	White	68 W	7 349 lm	4000 K, Ra > 83	L1900xB70xH80 mm	Wire / Direct

Technical data

Bred



Smal



Installation	Wire / Direct
Color temp. LED **MacAdam**	3000 K / 4000 K 3 SDCM
Led life 68 W - 8000 LM	L_{80} B_{10} > 50 000 h L_{70} B_{10} > 80 000 h
Connection **Lumen-out** **Nominell voltage**	2 x 5-pole terminal 7 349 lm (4000 K) 230/240 V, 50 Hz
Number/Fuse	10 A type C = 24 pcs 16 A type C = 40 pcs
Protection class	IP 22. CE-approved.



Caleidoscope®