



expoLED G2 - 8000

Powerful LED pendant luminaire for wire suspension.

Including 5.0 M cable and earthed plug.

Pendant made of pressurized aluminium.
Powderpainted with fine matt texture colour.


High color reproduction and consistent light image.
Color temperature 3000 K or 4000 K.

Passive cooling of LED chip for optimal service life and reliability.

Material
Colour temp [K]
Design LED life
CRI
Initial MacAdam
Nominal Voltage
Form protection
Weight

Pressurized aluminium
3000 K / 4000 K
L70 B50 > 50 000 h (T_a 25°)
80
3 SDCM
230/240 V, 50 Hz
IP 20, Class I, CE-approved
8,6 kg

Dimensions [mm]



Colours



Item No.	Description	Painting colour	Power	Lumen output	EEC	LED Colour	Amount/Fuse 16 A C-type	Amount/Fuse 10 A C-type
170728-830-0101	expoLED G2 8000 Flood	White	83 W	7 522 lm	A+	3000 K	28	18
170728-830-0102	expoLED G2 8000 Flood	Grey	83 W	7 522 lm	A+	3000 K	28	18
170728-830-0103	expoLED G2 8000 Flood	Black	83 W	7 522 lm	A+	3000 K	28	18
170728-840-0101	expoLED G2 8000 Flood	White	83 W	7 890 lm	A+	4000 K	28	18
170728-840-0102	expoLED G2 8000 Flood	Grey	83 W	7 890 lm	A+	4000 K	28	18
170728-840-0103	expoLED G2 8000 Flood	Black	83 W	7 890 lm	A+	4000 K	28	18

Caleidoscope

Östra Sandgatan 14 - 252 27 Helsingborg - Sweden - sales@caleidoscope.se - www.caleidoscope.se - Tel +46(0)42 311 18 10