

# Modus 60120



Energy efficient LED general light fixture for mounting in T24 ceiling profile with module 600x1200 mm.

Equipped with 2 parallel double-parabolic reflectors with selectable optics for ceiling heights between 2.5 to 4 meters (narrow or flood reflector). High UGR-levels.

Standard RAL 9010. Optional RAL color on request.

By selecting the corresponding drive unit, luminaires can be obtained in different lumen packages / wattage.

Protection class IP20.

5-year LED Warranty.

Art. No:	Description	Colour	Power	Lumen Out	CCT (Kelvin)	Dimension	System
170130 830 60120 01	modus 60120, 830, 2500-5832 lm, Flood	White	20 - 50 W	2500 - 5832 lm	3000 K, Ra > 83	L1193xB97xH33 mm	T24 600x1200
170130 830 60120 21	modus 60120, 830, 2500-5832 lm, Narrow	White	20 - 50 W	2500 - 5832 lm	3000 K, Ra > 83	L1193xB97xH33 mm	T24 600x1200
170130 835 60120 01	modus 60120, 835, 2500-5832 lm, Flood	White	20 - 50 W	2500 - 5832 lm	3500 K, Ra > 83	L1193xB97xH33 mm	T24 600x1200
170130 835 60120 21	modus 60120, 835, 2500-5832 lm, Narrow	White	20 - 50 W	2500 - 5832 lm	3500 K, Ra > 83	L1193xB97xH33 mm	T24 600x1200
170130 840 60120 01	modus 60120, 840, 2500-5832 lm, Flood	White	20 - 50 W	2500 - 5832 lm	4000 K, Ra > 83	L1193xB97xH33 mm	T24 600x1200
170130 840 60120 21	modus 60120, 840, 2500-5832 lm, Narrow	White	20 - 50 W	2500 - 5832 lm	4000 K, Ra > 83	L1193xB97xH33 mm	T24 600x1200
161005 500	Driver unit 500 mA with quick connection for luminaire and 3.0 meter cord with plug.		20 W	2500 lm (3000 K)			
161005 700	Driver unit 700 mA with quick connection for luminaire and 3.0 meter cord with plug.		30 W	3322 lm (3000 K)			
161005 1050	Driver unit 1050 mA with quick connection for luminaire and 3.0 meter cord with plug.		40 W	4827 lm (3000 K)			
161005 1300	Driver unit 1300 mA with quick connection for luminaire and 3.0 meter cord with plug.		50 W	5832 lm (3000 K)			

## Technical data

<b>Installation</b>	T24 profile with module 600x1200	<b>Number / fuse</b>	10 A type C = 24 pcs 16 A type C = 40 pcs
<b>Färg temp LED Chip</b>	3000 K / 3500 K / 4000 K	<b>Protection class</b>	IP 20. CE-Approved.
<b>MacAdam</b>	3 SDCM		

<b>LED info 20-50 W</b>	$L_{80} B_{10}$ 50 000 h $(T_o 25^\circ)$
	$L_{70} B_{10}$ 80 000 h $(T_o 25^\circ)$

<b>Connection</b>	3,0 meter cabel with 2-pin cord
<b>Lumen</b>	2500 - 5832 lm (3000 K)
<b>Rated voltage</b>	230/240 V, 50 Hz
<b>DALI</b>	On request.

