



capellaLED

LED spotlight with outstanding colour rendering of CRI 97 level and very high anti-glare with black reflector ring inside.


Lightfixture body made of aluminium. Passive cooling of the LED chip for optimum service life and reliability.

Lens and reflector that creates a well-balanced light pattern with very high efficiency.

Material
Colour temp [K]
Design LED life
CRI
Initial MacAdam
Power
Nominal Voltage
Form protection
Weight

Die-cast aluminium
 3000 K Vivid Natural
 L70 B10 > 50 000 h (T_a 25°)
 97
 2 SDCM
 30 W
 230/240 V, 50 Hz
 IP 20, Class I, CE-approved
 1,3 kg

Dimensions [mm]



Colours [*]

1 2 3



Item No.	Description	Painting colour	Power	Lumen output	EEC	LED Colour temperature	Amount/Fuse 16 A C-type	Amount/Fuse 16 A B-type
180601-930-120[*]	capellaLED, 930 Vivid, Spot 12°	[*]	28 W	2600 lm	A+	3000 K B BBL	51	32
180601-930-240[*]	capellaLED, 930 Vivid, Medium 24°	[*]	28 W	2600 lm	A+	3000 K B BBL	51	32
180601-930-380[*]	capellaLED, 930 Vivid, Flood 38°	[*]	28 W	2600 lm	A+	3000 K B BBL	51	32

Caleidoscope