



## capellaLED Mini

Small sized LED spotlight with outstanding colour rendering of CRI 97 level and very high anit-glare with black reflector ring inside.


Lightfixture body made of aluminium. Passive cooling of the LED chip for optimum service life and reliability.

Lens and reflector that creates a well-balanced light pattern with very high efficiency.

**Material**  
**Colour temp [K]**  
**Design LED life**  
**CRI**  
**Initial MacAdam**  
**Power**  
**Nominal Voltage**  
**Form protection**  
**Weight**

Die-cast aluminium  
 3000 K Vivid Natural  
 L70 B10 > 50 000 h (T<sub>a</sub> 25°)  
 97  
 3 SDCM  
 11 W  
 230/240 V, 50 Hz  
 IP 20. Class I. CE-approved  
 1,0 kg

**Dimensions [mm]**



**Colours [\*]**

1

2

3



Item No.	Description	Painting colour	Power	Lumen output	EEC	LED Colour temperature	Amount/Fuse 16 A C-type	Amount/Fuse 16 A B-type
180401-930-120[*]	capellaLED Mini, 930 Vivid, Spot 12°	[*]	11 W	1000 lm	A+	3000 K B BBL	60	40
180401-930-240[*]	capellaLED Mini, 930 Vivid, Medium 24°	[*]	11 W	1000 lm	A+	3000 K B BBL	60	40
180401-930-380[*]	capellaLED Mini, 930 Vivid, Flood 38°	[*]	11 W	1000 lm	A+	3000 K B BBL	60	40

# Caleidoscope