capellaLED Mini

Small sized LED spotlight with outstanding colour rendering of CRI +90 level and very high anit-glare with black reflector ring inside.

Lightfixture body made of aluminium. Passive cooling of the LED chip for optimum service life and reliability.

Lens and reflector that creates a well-balanced light pattern with very high efficiency.

Material	Die-cast aluminium
Colour temp [K]	3000 K B BBL
Design LED life	L70 B10 > 50 000 h (T_a 25°)
CRI	+90
Initial MacAdam	3 SDCM
Power	8 W
Nominal Voltage	230/240 V, 50 Hz
Form protection	IP 20. Class I. CE-approved
Weight	0,48 kg

Dimensions [mm]



Colours [*]

1

2

3

Item No.	Description	Painting colour	Power	Lumen output	EEC	LED Colour temperature	Amount/Fuse 16 A C-type	Amount/Fuse 16 A B-type
180401-930-120[*]	capellaLED Mini, 930 B BBL, Spot 12°	[*]	8 W	750 lm	A++	3000 K B BBL	60	40
180401-930-240[*]	capellaLED Mini, 930 B BBL, Medium 24°	[*]	8 W	750 lm	A++	3000 K B BBL	60	40
180401-930-380[*]	capellaLED Mini, 930 B BBL, Flood 38°	[*]	8 W	750 lm	A++	3000 K B BBL	60	40

Caleidoscope

Östra Sandgatan 14 - 252 27 Helsingborg - Sweden - sales@caleidoscope.se - www.caleidoscope.se - Tel +46(0)42 311 18 10