



dropLED Midi


Retractable and rotatable medium sized LED downlight.

Lightfixture body made of aluminium. Passive cooling of the LED chip for optimum service life and reliability.

Lens and reflector that creates a well balanced light pattern with very high efficiency.

Available in a variation of LED spectrum colours.

Including electronic gear with 3,0 meter cable and 2-pin plug.



Material
Colour temp [K]
Design LED life
CRI
Initial MacAdam
Power
Nominal Voltage
Form protection
Weight

Die-cast aluminium
 3000 K B BBL
 L70 B10 > 50 000 h (T_a 25°)
 90
 3 SDCM
 20 W
 230/240 V, 50 Hz
 IP 20, Class III. CE-approved
 1,0 kg

Dimensions [mm] / Saw instructions

ø 117 mm



Colours [*]

1

2

3



Item No.	Description	Painting colour	Power	Lumen output	EEC	LED Colour temperature	Amount/Fuse 16 A C-type	Amount/Fuse 16 A B-type
020-20930-120[*]	dropLED Midi, Spot 12°	[*]	20 W	1475 lm	A+	3000 K B BBL	51	32
020-20930-240[*]	dropLED Midi, Medium 24°	[*]	20 W	1475 lm	A+	3000 K B BBL	51	32
020-20930-380[*]	dropLED Midi, Flood 38°	[*]	20 W	1475 lm	A+	3000 K B BBL	51	32

Caleidoscope