



dropLED Mini

Retractable and rotatable small LED downlight.

Lightfixture body made of aluminium. Passive cooling of the LED chip for optimum service life and reliability.

Lens and reflector that creates a well balanced light pattern with very high efficiency.


Available in a variation of LED spectrum colours.

Including electronic gear with 3,0 meter cable and 2-pin plug.

Material
Colour temp [K]
Design LED life
CRI
Initial MacAdam
Power
Nominal Voltage
Form protection
Weight

Die-cast aluminium
3000 K B BBL
L70 B10 > 50 000 h (T_a 25°)
90
3 SDCM
10 W
230/240 V, 50 Hz
IP 20, Class III. CE-approved
1,0 kg

Dimensions [mm] / Saw instructions



Ø 78 mm



Colours [*]

1

2

3



Item No.	Description	Painting colour	Power	Lumen output	EEC	LED Colour temperature	Amount/Fuse 16 A C-type	Amount/Fuse 16 A B-type
020-10930-120[*]	dropLED Midi, Spot 12°	[*]	10 W	910 lm	A+	3000 K B BBL	51	32
020-10930-240[*]	dropLED Midi, Medium 24°	[*]	10 W	910 lm	A+	2700 K	51	32
020-10930-380[*]	dropLED Midi, Flood 38°	[*]	10 W	910 lm	A+	2700 K	51	32

Caleidoscope

Östra Sandgatan 14 - 252 27 Helsingborg - Sweden - sales@caleidoscope.se - www.caleidoscope.se - Tel +46(0)42 311 18 10