



## plainLED G4 Track

LED spotlight with global adapter with integrated LED driver for mounting on 3-phase track.

Lightfixture body made of aluminium. Passive cooling of the LED chip for optimal service life and reliability.


Deep reflector design in MIRO® Silver-material with very high efficiency that creates a well balanced and energyefficient lightpicture.

5-years warranty

**Material**  
**Colour temp [K]**  
**Design LED life**  
**CRI**  
**Initial MacAdam**  
**Nominal Voltage**  
**Form protection**  
**Weight**

Die-cast aluminium  
 3000 K B BBL other on request  
 L70 B10 > 50 000 h (T<sub>c</sub> 25°)  
 > 90  
 2 SDCM  
 230/240 V, 50 Hz  
 IP 20. Class I. CE-approved  
 1,0 kg

**Dimensions [mm]**



**Colours [\*]**



Item No.	Description	Painting colour	Power	Lumen output	EEC	LED Colour	Amount/Fuse 16 A C-type	Amount/Fuse 16 A B-type
016-93001-1501-TG4	plainLED G4 track, Spot 15°	White	25 W	2850 lm	A+	3000 K B BBL	51	32
016-93001-2001-TG4	plainLED G4 track, Medium 20°	White	25 W	2850 lm	A+	3000 K B BBL	51	32
016-93001-4001-TG4	plainLED G4 track, Flood 40°	White	25 W	2850 lm	A+	3000 K B BBL	51	32
016-93001-1502-TG4	plainLED G4 track, Spot 15°	Grey	25 W	2850 lm	A+	3000 K B BBL	51	32
016-93001-2002-TG4	plainLED G4 track, Medium 20°	Grey	25 W	2850 lm	A+	3000 K B BBL	51	32
016-93001-4002-TG4	plainLED G4 track, Flood 40°	Grey	25 W	2850 lm	A+	3000 K B BBL	51	32
016-93001-1503-TG4	plainLED G4 track, Spot 15°	Black	25 W	2850 lm	A+	3000 K B BBL	51	32
016-93001-2003-TG4	plainLED G4 track, Medium 20°	Black	25 W	2850 lm	A+	3000 K B BBL	51	32
016-93001-4003-TG4	plainLED G4 track, Flood 40°	Black	25 W	2850 lm	A+	3000 K B BBL	51	32

*Caleidoscope*