






plainLED G4 DOT™ Mini

LED-spotlight with unique combined driver and adaptor designed for quick and easy installation to Kaleidoscope grid ceiling systems.

The spotlight unit is attached by three strong neodymium magnets with permanent traction to the grid ceiling profile.



Material

Colour temp [K]
Design LED life
CRI
Lumen
Initial MacAdam
Nominal Voltage
Form protection
Weight
Colours

Mounting Dimensions

Die-cast aluminium and plastic housing
3000 K B BBL, 3500 K, 4000 K
L90 50 000 h (T_a 25°)
90
1020 lm
2 SDCM
230/240 V, 50 Hz
IP 20. Class III. CE-approved
0,48 kg
White, grey, black (others on request)
Steel profile x > 50 mm.
a = ø 58 mm
b = 85 mm



Item No.	Description	Painting colour	Power	Lumen output	Reflector	EEC	LED Colour	Amount/ Fuse 16 A C-type	Amount/ Fuse 16 A B-type
016-93001-**01-350-DOT-0a	plainLED G4 DOT™ Mini, 930 Below BBL - 3000 K	a = 1 = white a = 2 = grey a = 3 = black	14 W	1020 lm	* = 15° (Spot) * = 26° (Medium) * = 40° (Flood)	A+	3000 K Below BBL	68 pcs	40 pcs
016-93501-**01-350-DOT-0a	plainLED G4 DOT™ Mini, 935 - 3500 K	a = 1 = white a = 2 = grey a = 3 = black	14 W	1085 lm	* = 15° (Spot) * = 26° (Medium) * = 40° (Flood)	A+	3500 K	68 pcs	40 pcs
016-94001-**01-350-DOT-0a	plainLED G4 DOT™ Mini, 940 - 4000 K	a = 1 = white a = 2 = grey a = 3 = black	14 W	1105 lm	* = 15° (Spot) * = 26° (Medium) * = 40° (Flood)	A+	4000 K	68 pcs	40 pcs
031-010-01	Power Cable 4,0 m (2x0,72 mm2) 2 pin EU plug + IEC C7	White							
031-010-03	Power Cable 4,0 m (2x0,72 mm2) 2 pin EU plug + IEC C7	Black							
031-010-01-UK	Power Cable 4,0 m (2x0,72 mm2) 2 pin UK plug + IEC C7	White							
031-010-03-UK	Power Cable 4,0 m (2x0,72 mm2) 2 pin UK plug + IEC C7	Black							

Caleidoscope