






plainLED G4 DOT™ XL

LED-spotlight with unique combined driver and adaptor designed for quick and easy installation to Kaleidoscope grid ceiling systems.

The spotlight unit is attached by three strong neodymium magnets with permanent traction to the grid ceiling profile.



Material
Colour temp [K]
Design LED life
CRI
Lumen
Initial MacAdam
Nominal Voltage
Form protection
Weight
Colours:

Mounting
Dimensions

Die-cast aluminium / plastic
3000 K B BBL, 3500 K, 4000 K
L70 B10 > 50 000 h (T_a 25°)
> 90
3 950 lm
2 SDCM
230/240 V, 50 Hz
IP 20. Class III. CE-approved
1,05 kg
White, grey, black (others on request)
Steel profile x > 50 mm.
a = ø 117 mm
b = 120 mm



Item No.	Description	Painting colour	Power	Lumen output	Reflector	EEC	LED Colour	Amount/ Fuse 16 A C-type	Amount/ Fuse 16 A B-type
016-93001-**01-1050-DOT-0a	plainLED G4 DOT™ XL, 930 Below BBL - 3000 K	a = 1 = white a = 2 = grey a = 3 = black	43 W	3855 lm	* = 23° (Medium) * = 44° (Flood) * = 57° (X-Flood)	A	3000 K Below BBL	42 pcs	25 pcs
016-93501-**01-1050-DOT-0a	plainLED G4 DOT™ XL, 935 - 3500 K	a = 1 = white a = 2 = grey a = 3 = black	43 W	3825 lm	* = 23° (Medium) * = 44° (Flood) * = 57° (X-Flood)	A	3500 K	42 pcs	25 pcs
016-94001-**01-1050-DOT-0a	plainLED G4 DOT™ XL, 940 - 4000 K	a = 1 = white a = 2 = grey a = 3 = black	43 W	3895 lm	* = 23° (Medium) * = 44° (Flood) * = 57° (X-Flood)	A	4000 K	42 pcs	25 pcs
031-010-01	Power Cable 4,0 m (2x0,72 mm2) 2 pin EU plug + IEC C7	White							
031-010-03	Power Cable 4,0 m (2x0,72 mm2) 2 pin EU plug + IEC C7	Black							
031-010-01-UK	Power Cable 4,0 m (2x0,72 mm2) 2 pin UK plug + IEC C7	White							
031-010-03-UK	Power Cable 4,0 m (2x0,72 mm2) 2 pin UK plug + IEC C7	Black							

Caleidoscope