



atreaLED G4

LED downlight with deep reflector and body made of aluminium. Passive cooling of the LED chip for optimum service life and reliability.


Anodized aluminium reflector that creates a well balanced light pattern with very high efficiency.

Including electronic gear with quick connector and 3,0 meter main power cable with 2-pin european plug.

Material
Colour temp [K]
Design LED life
CRI
Initial MacAdam
Power
Nominal Voltage
Form protection
Weight

Die-cast aluminium
 3000 K B BBL other on request
 L90 50 000 h (T_a 25°)
 90
 3 SDCM
 28 W
 230/240 V, 50 Hz
 IP 20. Class III. CE-approved
 0,85 kg

Dimensions [mm]



∅ 150 mm



Colours **White** **Grey** **Black**



Item No.	Description	Painting colour	Power	Lumen output	EEC	LED Colour temperatur	Amount/Fuse 16 A C-type	Amount/Fuse 16 A B-type
191125-930-6001-G4	atreaLED, Flood 60°, 930 Below BBL, White	White	28 W	2600 lm	A+	3000 K B BBL	51	32
191125-930-6002-G4	atreaLED, Flood 60°, 930 Below BBL, White	Grey	28 W	2600 lm	A+	3000 K B BBL	51	32
191125-930-6003-G4	atreaLED, Flood 60°, 930 Below BBL, White	Black	28 W	2600 lm	A+	3000 K B BBL	51	32

Caleidoscope