



## optiLED G4

Adjustable LED downlight.

Lightfixture body made of aluminium. Passive cooling of the LED chip for optimum service life and reliability.

Lens and reflector that creates a well balanced light pattern with very high efficiency.

Available in a variation of LED spectrum colours.

Including electronic gear with quick connector and 3,0 meter main power cable with 2-pin european plug.

**Material**  
**Colour temp [K]**  
**Design LED life**  
**CRI**  
**Initial MacAdam**  
**Power**  
**Nominal Voltage**  
**Form protection**  
**Weight**

Die-cast aluminium  
 3000 K B BBL other on request  
 L90 50 000 h (T<sub>a</sub> 25°)  
 90  
 3 SDCM  
 28 W  
 230/240 V, 50 Hz  
 IP 20. Class I. CE-approved  
 0,85 kg

**Dimensions [mm]**

∅ 170 mm



**Colours [\*]**

**1. White**

**2. Grey**

**3. Black**



Item No.	Description	Painting colour	Power	Lumen output	EEC	LED Colour temperatur	Amount/Fuse 16 A C-type	Amount/Fuse 16 A B-type
150929-930-150[*]-G4	optiLED G4, Spot 15°, 930 B BBL, White	[* = 1, 2, 3]	28 W	2775 lm	A+	3000 K B BBL	51	32
150929-930-250[*]-G4	optiLED G4, Medium 25°, 930 B BBL, White	[* = 1, 2, 3]	28 W	2775 lm	A+	3000 K B BBL	51	32
150929-930-450[*]-G4	optiLED G4, Flood 45°, 930 B BBL, White	[* = 1, 2, 3]	28 W	2775 lm	A+	3000 K B BBL	51	32
150929-930-630[*]-G4	optiLED G4, X-Flood 63°, 930 B BBL, White	[* = 1, 2, 3]	28 W	2775 lm	A+	3000 K B BBL	51	32

*Caleidoscope*