



dropLED G4

Retractable and rotatable LED downlight.

Lightfixture body made of aluminium. Passive cooling of the LED chip for optimum service life and reliability.

Lens and reflector that creates a well balanced light pattern with very high efficiency.


Available in a variation of LED spectrum colours.

Including electronic gear with quick connector and 3,0 meter main power cable with 2-pin european plug.

Material
Colour temp [K]
Design LED life
CRI
Initial MacAdam
Power
Nominal Voltage
Form protection
Weight

Die-cast aluminium
3000 K B BBL
L70 B10 > 50 000 h (T_a 25°)
90
3 SDCM
28 W
230/240 V, 50 Hz
IP 20. Class III. CE-approved
1,0 kg

Dimensions [mm] / Saw instructions



ø 140 mm



Colours

White (*=1)

Grey (*=2)

Black (*=3)



Item No.	Description	Painting colour	Power	Lumen output	EEC	LED Colour temperature	Amount/Fuse 16 A C-type	Amount/Fuse 16 A B-type
191127-930-150[*]-G4	dropLED G4, Spot 15°, 930 B BBL, White	[* = 1, 2, 3]	28 W	2775 lm	A+	3000 K B BBL	51	32
191127-930-250[*]-G4	dropLED G4, Medium 25°, 930 B BBL, White	[* = 1, 2, 3]	28 W	2775 lm	A+	3000 K B BBL	51	32
191127-930-450[*]-G4	dropLED G4, Flood 45°, 930 B BBL, White	[* = 1, 2, 3]	28 W	2775 lm	A+	3000 K B BBL	51	32
191127-930-600[*]-G4	dropLED G4, X-Flood 60°, 930 B BBL, White	[* = 1, 2, 3]	28 W	2775 lm	A+	3000 K B BBL	51	32

Caleidoscope

Östra Sandgatan 14 - 252 27 Helsingborg - Sweden - sales@caleidoscope.se - www.caleidoscope.se - Tel +46(0)42 311 18 10