



## dropLED G4

Retractable and rotatable LED downlight.

Lightfixture body made of aluminium. Passive cooling of the LED chip for optimum service life and reliability.

Lens and reflector that creates a well balanced light pattern with very high efficiency.

Available in a variation of LED spectrum colours.


Including electronic gear with quick connector and 3,0 meter main power cable with 2-pin european plug.

**Material**  
**Colour temp [K]**  
**Design LED life**  
**CRI**  
**Initial MacAdam**  
**Power**  
**Nominal Voltage**  
**Form protection**  
**Weight**

Die-cast aluminium  
 3000 K B BBL  
 L90 50 000 h (T<sub>a</sub> 25°)  
 90  
 3 SDCM  
 28 W  
 230/240 V, 50 Hz  
 IP 20. Class III. CE-approved  
 1,0 kg

**Dimensions [mm] / Saw instructions**

∅ 140 mm



**Colours**

**White (\*=1)**

**Grey (\*=2)**

**Black (\*=3)**



Item No.	Description	Painting colour	Power	Lumen output	EEC	LED Colour temperature	Amount/Fuse 16 A C-type	Amount/Fuse 16 A B-type
191127-930-150[*]-G4	dropLED G4, Spot 15°, 930 B BBL, White	[* = 1, 2, 3]	28 W	2775 lm	A+	3000 K B BBL	51	32
191127-930-250[*]-G4	dropLED G4, Medium 25°, 930 B BBL, White	[* = 1, 2, 3]	28 W	2775 lm	A+	3000 K B BBL	51	32
191127-930-450[*]-G4	dropLED G4, Flood 45°, 930 B BBL, White	[* = 1, 2, 3]	28 W	2775 lm	A+	3000 K B BBL	51	32
191127-930-600[*]-G4	dropLED G4, X-Flood 60°, 930 B BBL, White	[* = 1, 2, 3]	28 W	2775 lm	A+	3000 K B BBL	51	32

*Caleidoscope*