



dropLED G5

Retractable and rotatable LED downlight.

Lightfixture body made of aluminium. Passive cooling of the LED chip for optimum service life and reliability.

Lens and reflector that creates a well balanced light pattern with very high efficiency.

Available in a variation of LED spectrum colours.

Including electronic gear with quick connector and 3,0 meter main power cable with 2-pin european plug.

Material

Colour temp [K]

Design LED life

CRI

Initial MacAdam

Power

Nominal Voltage

Form protection

Weight

Die-cast aluminium

3000 K B BBL

L90 50 000 h (T_a 25°)

90

3 SDCM

23 W / 600 mA


230/240 V, 50 Hz

IP 20, Class III, CE-approved

1,0 kg

Dimensions [mm] / Saw instructions

ø 140 mm



Colours

White (*=1)

Grey (*=2)

Black (*=3)



Item No.	Description	Reflector /Beam	Colour	Energy consumption	Lumen output	Colour temperature, CRI	Amount/ Fuse/ 16 A C-type	Amount/ Fuse/ 16 A B-type
191127-930-150[*]-G5	dropLED G4, Spot 15°, 930 B BBL, White	Spot 15°	[* = 1, 2, 3]	23 W	2832 lm	3000 K BBL, CRI > 90	51	32
191127-930-250[*]-G5	dropLED G4, Medium 25°, 930 B BBL, White	Medium 25°	[* = 1, 2, 3]	23 W	2832 lm	3000 K BBL, CRI > 90	51	32
191127-930-450[*]-G5	dropLED G4, Flood 45°, 930 B BBL, White	Flood 45°	[* = 1, 2, 3]	23 W	2832 lm	3000 K BBL, CRI > 90	51	32
191127-930-600[*]-G5	dropLED G4, X-Flood 60°, 930 B BBL, White	X-Flood 60°	[* = 1, 2, 3]	23 W	2832 lm	3000 K BBL, CRI > 90	51	32

Caleidoscope

Östra Sandgatan 14 - 252 27 Helsingborg - Sweden - sales@caleidoscope.se - www.caleidoscope.se - Tel +46(0)42 311 18 10