






plainLED G5 DOT

LED-spotlight with unique combined driver and adaptor designed for quick and easy installation to Kaleidoscope grid ceiling systems.

The spotlight unit is attached by three strong neodymium magnets with permanent traction to the grid ceiling profile.



Material

Colour temp [K]

Design LED life

CRI

Lumen

Initial MacAdam

Nominal Voltage

Form protection

Weight

Colours

Mounting

Dimmable

Dimensions

Die-cast aluminium and plastic housing

3000 K B BBL, 3500 K B BBL, 4000 K

L90 > 50 000 h (T₀ 25°)

> 90

2910 lm

2 SDCM

230/240 V, 50 Hz

IP 20, Class III, CE-approved

0,67 kg

White, grey, black (others on request)

Steel profile x > 50 mm.

No

a = ø 80 mm

b = 105 mm



Item No.	Description	Painting colour	Power	Lumen output	Reflector	LED Colour	Amount/Fuse 16 A C-type	Amount/Fuse 16 A B-type
016-93001-**01-600-DOT-0a	plainLED G5 DOT™ 930 Below BBL - 3000 K	a = 1 = white a = 2 = grey a = 3 = black	23 W	2910 lm	* = 10° (Spot) * = 22° (Medium) * = 38° (Flood) * = 53° (X-Flood)	3000 K Below BBL	68 pcs	40 pcs
016-93501-**01-600-DOT-0a	plainLED G5 DOT™ 935 Below BBL - 3500 K	a = 1 = white a = 2 = grey a = 3 = black	23 W	2910 lm	* = 10° (Spot) * = 22° (Medium) * = 38° (Flood) * = 53° (X-Flood)	3500 K	68 pcs	40 pcs
016-94001-**01-600-DOT-0a	plainLED G5 DOT™ 940 - 4000 K	a = 1 = white a = 2 = grey a = 3 = black	23 W	2910 lm	* = 10° (Spot) * = 22° (Medium) * = 38° (Flood) * = 53° (X-Flood)	4000 K	68 pcs	40 pcs
031-010-01	Power Cable 4,0 m (2x0,72 mm ²) 2 pin EU plug + IEC C7	White						
031-010-03	Power Cable 4,0 m (2x0,72 mm ²) 2 pin EU plug + IEC C7	Black						
031-010-01-UK	Power Cable 4,0 m (2x0,72 mm ²) 2 pin UK plug + IEC C7	White						
031-010-03-UK	Power Cable 4,0 m (2x0,72 mm ²) 2 pin UK plug + IEC C7	Black						

Caleidoscope