



plainLED G5 Track

LED-spotlight with global adapter for mounting in 3-phase rail. Spotlight body made of aluminum die-castings.

Passive cooling of the LED chip for optimal lifetime and reliability. 7-years warranty.

MIRO Silver reflector technology that creates a well-balanced light image with very high efficiency.

Driver built into the global 3-phase adapter.

Color: white, black or grey (other on request)



Material
Colour temp [K]
Design LED life
CRI
UGR
System lumen
Initial MacAdam
Nominal Voltage
Form protection
Weight
Colours

Warranty


Accessories

Dimensions

Die-cast aluminium
 3000 K B BBL, 3500 K B BBL, 4000 K
 L90 > 50 000 h (T_a 25°)
 > 90
 < 5
 2 950 lm (23 W)
 2 SDCM
 230/240 V, 50/60 Hz
 IP 20. Class III. CE-approved
 0,475 kg
 White, grey, black (others on request)
 7-years

Honeycomb, **016H-TG5**
 Barndoors, **016B-TG5**

a = ø 80 mm
 b = 127 mm
 c = 170 mm



Item No.	Description	Painting colour	Power (System)	Lumen output (System)	Reflector	LED Colour	Amount/ Fuse 16 A C-type	Amount/ Fuse 16 A B-type
016-93001-**0(a)-TG5	plainLED G5 Track, 930 B BBL	a = 1 = white a = 2 = grey a = 3 = black	23 W	2950 lm	* = 10° (Spot) * = 22° (Medium) * = 38° (Flood) * = 53° (X-Flood)	3000 K Below BBL	68 pcs	40 pcs
016-93501-**0(a)-TG5	plainLED G5 Track, 935 B BBL	a = 1 = white a = 2 = grey a = 3 = black	23 W	2950 lm	* = 10° (Spot) * = 22° (Medium) * = 38° (Flood) * = 53° (X-Flood)	3500 K Below BBL	68 pcs	40 pcs
016-94001-**0(a)-TG5	plainLED G5 Track, 940	a = 1 = white a = 2 = grey a = 3 = black	23 W	2950 lm	* = 10° (Spot) * = 22° (Medium) * = 38° (Flood) * = 53° (X-Flood)	4000 K	68 pcs	40 pcs

Caleidoscope