



smartLED Track

LED spotlight with a adapter for mounting on a 3-phase track rail. The spotlight housing is made of die-cast recycled aluminium.

Passive cooling of the LED chip ensures optimal service life and reliability. The product is covered by a 7-year warranty.

Equipped with MIRO-SILVER® reflector technology, providing a well-balanced light distribution and very high efficiency.

Available colours: white, black or grey. Other colours are available upon request.


Material
Colour temp [K]
Design LED life
CRI
System lumen
Initial MacAdam
Nominal Voltage
Form protection
Weight
Colours

Warranty


Dimensions

Die-cast aluminium
 3000 K, 3500 K, 4000 K
 L90 > 50 000 h (T_a 25°)
 > 90
 3040 lm
 2 SDCM
 230/240 V, 50/60 Hz
 IP 20, Class III, CE-approved
 0,475 kg
 White, grey, black (others on request)
 7-years

Accessories



016B-TG5-01 016B-TG5-03



Item No.	Description	Painting colour	Power (System)	Lumen output (System)	Reflector	LED Colour	Amount/ Fuse 16 A C-type	Amount/ Fuse 16 A B-type
228 930 22 0(*) TG3	smartLED™ G3 Track, Medium 22°, 930 BBL, white	α = 1 = white α = 2 = grey α = 3 = black	19 W (400 mA)	3040 lm	* = 10° (Spot) * = 22° (Medium) * = 38° (Flood) * = 53° (X-Flood)	3000 K Below BBL	68 pcs	40 pcs
228 935 22 0(*) TG3	smartLED™ G3 Track, Medium 22°, 935 BBL, white	α = 1 = white α = 2 = grey α = 3 = black	19 W (400 mA)	3040 lm	* = 10° (Spot) * = 22° (Medium) * = 38° (Flood) * = 53° (X-Flood)	3500 K Below BBL	68 pcs	40 pcs
228 940 22 0(*) TG3	smartLED™ G3 Track, Medium 22°, 940, white	α = 1 = white α = 2 = grey α = 3 = black	19 W (400 mA)	3040 lm	* = 10° (Spot) * = 22° (Medium) * = 38° (Flood) * = 53° (X-Flood)	4000 K	68 pcs	40 pcs

Caleidoscope